



Pipettors, variable volume, multichannel, Thermo Scientific Finn timer® F2

04

Thermo
SCIENTIFIC



- Advanced volume gearing mechanism to improve accuracy and precision
- Fully autoclavable
- Double action pipetting button with rotating upper part independent of volume setting
- Large ergonomics display
- Light pipetting action
- 'Super Blow Out' mechanism and soft touch tip ejection

Technical Specification - Specific

	PMP-020-100P	PMP-020-105F	PMP-020-110M	PMP-020-115C	PMP-020-120J
Volume, µL	10; 5; 1	50; 25; 5	100; 50; 10	300; 150; 30	10; 5; 1
Inaccuracy, %	± 2.4; ± 4.0; ± 12.0	± 1.5; ± 2.5; ± 5.0	± 1.3; ± 2.5; ± 5.0	± 1.0; ± 1.5; ± 5.0	± 2.4; ± 4.0; ± 12.0
Imprecision, cv%	1.60; 3.00; 8.00	0.70; 1.20; 2.00	0.50; 1.20; 2.00	0.50; 1.20; 2.00	1.60; 3.00; 8.00

	PMP-020-125W	PMP-020-130G	PMP-020-135T	PMP-020-140D	PMP-020-145Q
Volume, µL	50; 25; 5	100; 50; 10	300; 150; 30	10; 5; 1	50; 25; 5
Inaccuracy, %	± 1.5; ± 2.5; ± 5.0	± 1.3; ± 2.5; ± 5.0	± 1.0; ± 1.5; ± 5.0	± 2.4; ± 4.0; ± 12.0	± 1.5; ± 2.5; ± 5.0
Imprecision, cv%	0.70; 1.20; 2.00	0.50; 1.20; 2.00	0.30; 0.50; 2.00	1.60; 3.00; 8.00	0.70; 1.20; 2.00



Catalogue No	Alt. No	Volume range, µL	No. of channels	Increments, µL	Colour code	Finntip
PMP-020-100P	4662000	1 to 10	8	0.02	Pink	Flex 10, 10, 50
PMP-020-105F	4662010	5 to 50	8	0.1	Yellow	Flex 200, 250 Univ, 200 Ext
PMP-020-110M	4662020	10 to 100	8	0.2	Yellow	Flex 200, 250 Univ, 200 Ext
PMP-020-115C	4662030	30 to 300	8	1	Orange	Flex 300, 300
PMP-020-120J	4662040	1 to 10	12	0.02	Pink	Flex 10, 10, 50
PMP-020-125W	4662050	5 to 50	12	0.1	Yellow	Flex 200, 250 Univ, 200 Ext
PMP-020-130G	4662060	10 to 100	12	0.2	Yellow	Flex 200, 250 Univ, 200 Ext
PMP-020-135T	4662070	30 to 300	12	1	Orange	Flex 300, 300
PMP-020-140D	4662080	1 to 10	16	0.02	Purple	Flex 10 (384), 50
PMP-020-145Q	4662090	5 to 50	16	0.1	Turquoise	50

Accessories

Catalogue No	Alt. No	Description
PMP-010-500G	9420400	Pipettor F-stand, 6 position