Flowmeters / Fume cabinets / Funnels



Flowmeters, polystyrene, Roto-Flo

- Easy to install, brightly coloured spinning wheels enabling quick visualisation of flow
- Minimum flow: 0.5L/min Maximum flow: 10L/min
- Internal flow channel diameter is 5mm, paddle wheel shell is 25mm, overall length is 51mm
- Maximum recommended pressure: 10psi
- Not for use with corrosive chemicals or fluids with temperature in excess of 64°C

Catalogue No Description FJE-200-030S 4 to 7mm, straight tube ends with blue wheel colour FJE-200-050M 4 to 7mm, barbed tube ends with red wheel colour FJE-200-070G 7 to 11mm, barbed tube ends with green wheel colour



Funnels, soda lime glass, conical Fisherbrand

Catalogue No FB56630 FB56631 FB56632 FB56633 FB56634	Top dia., mm 35 45 50 55	Stem length, mm 40 45 50 55 60
FB56634 FB56635	60 70	60 70
FB56636	100	100



Fume cabinets, T400

- Mobile fume cabinet tested to meet BB88 standard designed to give pupils and staff maximum benefit from practical chemistry and science at work
- COSHH compliant
- Carbon technology removes fumes at source removing the need for ducting
- Constructed from high quality materials
- Extended filter life

Technical Specification

Filters 1 x 22kg 'ED' filter 1 x particulate prefilter: 95% efficient at 0.5µm >400 Airflow, m³/hr Face velocity, m/sec >0.5 Fan Centrifugal (brushless + sparkless to IP44) <55 Noise level, dB (A) Lighting 2 x 30W fluorescent tubes (optional) 240V/50Hz Electrical Auxiliary power Double 13 amp socket Power 230W plus 3 amp fused auxiliary sockets Controls ON/OFF switch

Light switch (on optional module)

Low airflow indicator Hour meter

Construction Epoxy powder coated zintec steel

Acrylic panels and door

GRP worksurface with optional moulded drip cup

Dimensions

frame

Height, mm 1,820 (without light option:1,730) Width, mm 1,040 (including handles:1,120)

Depth, mm 680

Height of aperture, mm 400

Catalogue No Description BPG-160-010V Cabinet

BPG-160-020X Cabinet fitted with gas and water taps

NOTE: Please note items are 50kg +. Delivery to ground floor only. Any other requirements please request a quotation for delivery costs.